




Valtek ShearStream Segmented Ball Valve Series



Experience In Motion



Effective control for demanding flows. After more than one hundred years of close cooperation with our customers, we at Flowserve know what it is all about. Our robust valve and actuators, together with our advanced positioners, are designed to cope with the demands and control of all types of flowing media. With the focus on performance. Flowserve's products are compact, modular-built, high performance packages that are optimized for exact control and cost-

effective continuous operation. They have an extremely long life span as all parts are of highest quality. And they'll still be safe in the future as they use advanced technology and innovative solutions. Flowserve ensures a safe and cost-effective operation for our customers all over the world



Valtek ShearStream SB



Valtek ShearStream HP



Applications

High capacity, large turndown, moderate pressure drops, economical usage
High flow rates based on unrestricted straight-through port

General Services

- When Globe- or Butterfly Valves are not suitable
- Chemical Industry – general services
- Petrochemical Industry – high temperatures, low emissions
- General Industries – Water, Oil, Gas

More Severe Services

- Abrasive, erosive and corrosive applications
- Slurry, 2-phase Flow
- Liquid or pneumatic conveying
- Pulp, ash sluice water, plastic granules etc.

Valtek Positioner Options



XL

Extreme accuracy dual-stage analog, electropneumatic / pneumatic positioner. Explosionproof or Intrinsically safe.



Logix 500si Series

Economical compact user friendly digital positioner. With or without communication. Intrinsically safe.



Logix 3000IQ Series

Full-featured double acting, high volume digital positioner with HART or Foundation Fieldbus communication. Explosionproof or Intrinsically safe.

Valtek ShearStream SB

The excellent control characteristic of ShearStream SB are particularly beneficial in general control conditions found in the Process- and Chemical Industry. This is a default choice for standard applications, standard material selections and for moderate pressure ratings

Features

- Direct mounting of Turnex actuator
- One piece body
- Multiple packing options
- Tight shut-off
- Seat options
- Easy maintenance
- Characterized Ball Sector

Specification

Material	Carbon Steel (WCB) Stainless Steel (CF8M)
Sizes	ANSI 1" to 20" DIN DN25 to DN500
Pressure Classes	ANSI Class 150 to Class 300 DIN PN10 to PN40
End Connections	Flanged ANSI 1" to 20" / DIN DN25 to DN500 Wafer ANSI 1" to 8" / DIN DN25 to DN200



Options

ShearStream SB with Z-Trim

Works perfectly for steam regulation.
ShearStream SB-Z can be used in a wide variety of applications and meets the highest demands for control accuracy.

The unique Z-Trim design reduces noise and avoids cavitation by taking the pressure drop in several steps. The Z-trim is self-cleaning so it can also be used with slurries.



Environmental Packing

SafeGuard packing set is an approved, tested and certified packing arrangement in accordance with ISO 15848-1.

Turnex - Actuator package

Heavy duty actuator for high performance control. Turnex has a swing-link mechanism for scotch-yoke torque characteristics with no back-lash. Available as single- and double acting, fail open or fail close.

Direct mounted to Valve, Positioner, Solenoid Valves, Limit Switches.

Compact actuator with low mass for easy mounting.

Maintenance free for a long life

Integrated air channels.

Splines for different stem diameters.

Torque range of 74 – 14,750 lbs. ft. at 75 psi.



Valtek ShearStream HP

“Robust” describes Valtek ShearStream HP Segmented Ball Valve. Designed to overcome the problems of harsh, particle entrained processes, ShearStream HP also provides accurate, reliable control in a broad range of applications such as chemical, power and petro-chemical.

Features

- One piece body
- Segmented V-notch ball
- Heavy duty seat option
- Bi-directional flexible metal seat
- Flanged or wafer bodies
- Designed for higher pressure classes

Specification

Material	Carbon Steel (WCB) Stainless Steel (CF8M) Other Alloys (Monel, Hastelloy B/C, Alloy 20, Titanium etc.)
Sizes	ANSI 1" to 16"
Pressure Classes	ANSI Class 150 to Class 600
End Connections	Flanged , Wafer



Seat Options

Flexible Metal Seat


The flexible metal seat uses the pressure drops across the seal to enhance its shut-off characteristics in both directions.

Soft Seat


The Soft Seat utilizes PTFE or PEEK soft seat inserts. The soft seat is also available with a metal back-up seal.

Heavy Duty Seat

For applications requiring high pressure drops, the heavy duty seat provides tight shut-off and reliability. The sealed wave spring gives the seat consistent seating pressure that is long-lasting. The soft seat option for the Heavy Duty seat utilizes an UHMWPE insert.



Metal seat



Soft seat

Valtek – Spring Cylinder Rotary Actuator

The Valtek spring cylinder rotary actuator combines high torque and pneumatic stiffness with excellent throttling capabilities. These characteristics are designed into a lightweight, robust and compact assembly, making the Valtek rotary actuator the foremost choice for ShearStream HP.



Flowserve Corporation

Flow Control
1350 N. Mt. Springs Parkway
Springville, UT 84663
USA
Phone: +1 801 489 8611
Fax: +1 801 489 3719

Flowserve (Austria) GmbH

Control Valves - Villach Operation
Kasernengasse 6
9500 Villach
Austria
Phone: +43 (0)4242 41181 0
Fax: +43 (0)4242 41181 50

Flowserve India Controls Pvt. Ltd

Plot # 4, 1A, E.P.I.P, Whitefield
Bangalore Karnataka
India 560 066
Phone: +91 80 284 10 289
Fax: +91 80 284 10 286

NAF AB

Gelbgjutaregatan 2
SE-581 87 Linköping
Sweden
Phone: +46 (0)13 31 61 00
Fax: +46 (0)13 13 60 54

Quick Response Centers

Flowserve Deer Park

5114 Railroad Street
Deer Park, TX 77536 USA
Phone: 281 479 9500
Fax: 281 479 8511

Flowserve Baton Rouge

12134 Industriplex Blvd
Baton Rouge, LA 70809
Phone: 225-751-9880
Fax: 255-755-0728


Flowserve Philadelphia

104 Chelsea Parkway
Boothwyn, PA 19061 USA
Phone: 610 497 8600
Fax: 610 497 6680

Flowserve Singapore

12 Tuas Aventure 20
Rep. of Singapore 638824
Phone: (65) 68-798-900
Fax: (65) 68-624-940

To find your nearest sales location visit: www.flowserve.com/SalesLocator



FCD VLENBR0027-01 01.11 All data subject to change without notice.

©10.2007 Flowserve Corporation. Flowserve and Valtek are trademarks of Flowserve Corporation